

Mobil SHC Cibus Series

High Performance NSF H1 Registered Lubricants for Food Machinery

Product Description

Mobil SHC Cibus Series lubricants are supreme performance hydraulic, compressor, gear and bearing oils designed to provide outstanding equipment protection, long oil life and problem-free operation in the food and beverage processing and packaging industries. They are formulated from FDA and NSF registered hydrocarbon base fluids and additives. The combination of the naturally high viscosity index and the proprietary additive system enables the Mobil SHC Cibus series lubricants to provide outstanding performance in a wide range of service applications at high and low temperatures, high loading and in areas of high wash-down well beyond the capabilities of typical mineral oils.

Mobil SHC Cibus lubricants are NSF H1 registered lubricants and also comply with Title 21 CFR 178.3570 by the Food and Drug Administration (USA) for lubricants with incidental food contact and is accepted by the Canadian Food Inspection Agency for use in food processing facilities. They are also suitable for Kosher and Halal food preparation for multi faith applications and to offer processing engineers maximum flexibility during operations. The products are colourless with low odour and are formulated to be free of animal derived materials and allergens from nuts, wheat or gluten.

The Mobil SHC Cibus Series products have low traction coefficients, derived from the molecular structure of the base stocks used. This results in low fluid friction in the load zone of non-conforming surfaces. Low fluid friction produces lower operating temperatures and improved equipment efficiency, which potentially translates into reduced power consumption. The carefully engineered products also help to extend the service life of machinery components and allows for more economical equipment design. Moreover, the additive system used in these oils has been selected to provide good wear protection, excellent oxidation stability, protection against rust and corrosion even in moist environments and provide good system cleanliness. The Mobil SHC Cibus Series oils are also compatible with seals and other construction materials used in equipment normally lubricated with mineral oils.

The Mobil SHC Cibus Series oils can be used as hydraulic, gear, bearing and circulating oils in all areas within the food processing plant and can be included as part of a HACCP plan. The products meet the most rigorous performance requirements of a range of component manufacturers using various multi-metallurgy designs that help allow a single product series to lubricate effectively. Because they offer productivity and NSF H1 registration benefits, the Mobil SHC Cibus products can be used both above and below the processing line to reduce inventory costs and reduce the risks of non H1 registered lubricants being dispensed in high contamination risk areas.

Features and Benefits

The Mobil SHC brand of lubricants is recognised and appreciated around the world for innovation and outstanding performance. These molecular designed products based on synthetic materials symbolise the continuing commitment to use advanced technology to provide outstanding lubricant products. Not least among the benefits is the potential for efficiency improvements compared to mineral oils.

The Mobil SHC Cibus Series oils offer the following features and potential benefits.



Features	Advantages and Potential Benefits
NSF H1 registered lubricants	Allows use in food and beverage packaging and processing applications
High viscosity index	Maintains viscosity and film thickness at high temperatures to help protect equipment
	Exceptional low temperature performance, including low power consumption at start-up
High load carrying capability	Helps protect equipment and extend life
	Minimizes unexpected downtime and extends service periods
Good seal compatibility	Less contamination and lower potential oil leakage
Excellent oxidation stability	Provides long oil and equipment life
Excellent water separation and good corrosion protection	Prevents the internal system from corrosion even where large quantities of water are present
	Maintains lubrication performance even after high pressure wash downs
Meets a wide range of equipment requirements	Multi-service applications - One product can replace several
	Minimizes inventory requirements and reduced potential for product misapplication
Low traction coefficient	Reduces overall friction and can increase efficiency in sliding mechanisms, with potential for reduced power consumption and lower steady-state operating temperatures

Applications

Handling and Storage Recommendations It is recommended that Mobil SHC Cibus lubricants should be stored inside and segregated from other non NSF H1 lubricants. Ideally, they should be stored in a clearly signed, separate, designated inside area. Drums and pails should not be stacked below or above other non NSF H1 lubricants. New packaging should be free from damage with an unbroken seal. Record the delivery date, batch number and expiration date. Record the date of initial seal breakage and use the contents in time by suitable stock rotation. Close all package openings after use. Do not replace unused oil in the container. Use clearly labeled dedicated equipment for internal transportation. Label machinery with the name of the correct NSF H1 lubricant where appropriate.

Lubricant Changeover While the Mobil SHC Cibus Series may be physically compatible with other NSF H1 or non NSF H1 registered mineral oil based products, a mixture may detract from their performance and also from their registration status. Consequently it is recommended that before changing systems from non H1 lubricants to the Mobil SHC Cibus Series, or even for brand new equipment, the system should be thoroughly cleaned out and flushed to achieve the maximum performance benefits and to comply with H1 registration.

Applications Mobil SHC Cibus Series lubricants are recommended for use in a wide variety of hydraulic, compressor, gear and bearing applications within food and beverage processing, packaging and pharmaceuticals. The products are effective in many applications including those where maintenance costs of component replacement, system cleaning and lubricant changes are high.

- Mobil SHC Cibus 32, 46 and 68 are high performance fluids intended for hydraulic, circulating, compressor and vacuum pump applications

- Mobil SHC Cibus 150, 220, 320 and 460 are intended for gear, bearing and circulating systems

A suitable used oil analysis program, such as Signum from ExxonMobil, can help monitor the concentration of wear metals and provide information on appropriate actions.

Incidental Food Contact Only per FDA 21CFR 178.3570 Mobil SHC Cibus series lubricants are NSF H1 registered for incidental food contact only which means a limitation of 10ppm oil in food product per FDA 21CFR 178.3570. They are not to be used as direct food contact lubricants.

Specifications and Approvals

Meets or Exceeds the following industry specifications	Mobil SHC Cibus 32	Mobil SHC Cibus 46	Mobil SHC Cibus 68	Mobil SHC Cibus 150	Mobil SHC Cibus 220	Mobil SHC Cibus 320	Mobil SHC Cibus 460
FDA 21 CFR 178.3570	X	X	X	X	X	X	X
NSF H1	X	X	X	X	X	X	X
NSF Registered Number	141500	141498	141499	141502	141503	141505	141501
Kosher	X	X	X	X	X	X	X
Halal	X	X	X	X	X	X	X
Canadian Food Inspection Agency, acceptance	X	X	X	X	X	X	X
DIN 51524 HLP	X	X	X				
ISO 11158 HM	X	X	X				
DIN 51506 VDL	X	X	X				
DIN 51517 CLP				X	X	X	X

Typical Properties

	Mobil SHC Cibus 32	Mobil SHC Cibus 46	Mobil SHC Cibus 68	Mobil SHC Cibus 150	Mobil SHC Cibus 220	Mobil SHC Cibus 320	Mobil SHC Cibus 460
ISO Grade	32	46	68	150	220	320	460
Viscosity, ASTM D 445							
cSt @ 40°C	30	43	72	162	222	311	458
cSt @ 100°C	5.8	7.7	11.4	20.7	24.5	32.7	43.6
Viscosity Index, ASTM D 2270	140	148	151	150	139	147	148
Specific Gravity @ 15.6°C, ASTM D 4052	0.829	0.833	0.838	0.843	0.843	0.854	0.856
Copper Strip Corrosion, ASTM D 130	1B	1B	1B	1A	1B	1B	1B
Rust Characteristics Proc. A, ASTM D 665	Pass	Pass	Pass	Pass	Pass	Pass	Pass

	Mobil SHC Cibus 32	Mobil SHC Cibus 46	Mobil SHC Cibus 68	Mobil SHC Cibus 150	Mobil SHC Cibus 220	Mobil SHC Cibus 320	Mobil SHC Cibus 460
Pour Point, °C, ASTM D 97	-54	-51	-48	-21	-24	-42	-42
Flash Point, °C, ASTM D 92	253	258	267	226	274	284	294
FZG, DIN 51354, Fail Stage	12	12	12	13	13	13	13

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the applications referred to above and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contact office, or via the Internet. This product should not be used for purposes other than the applications referred to above. If disposing of used product, take care to protect the environment.

Mobil, Mobil SHC, Cibus and the Pegasus design are trademarks of Exxon Mobil Corporation or one of its subsidiaries.

ExxonMobil Lubricants & Specialties

All products may not be available locally. For more information, contact your local sales office or visit www.exxonmobil.com.

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil affiliate entities. Due to continual product research and development, the information contained herein is subject to change without notification. Typical Properties may vary slightly.

© 2007 Exxon Mobil Corporation. All rights reserved.