

Mobilgrease CM Series

Grease

Product Description

Mobilgrease CM Series products are a family of extra high performance extreme-pressure greases. Mobilgrease CM-P and CM-S are NLGI Grade 2, while Mobilgrease CM-W and CM-L are NLGI Grade 1. All four products are manufactured with a proprietary high-temperature, lithium complex thickener system. They exhibit excellent resistance to softening under severe working, and provide good adhesion and cohesion. An extreme-pressure additive provides exceptional protection against wear and shock loads, while additional additives enhance resistance to high-temperature oxidation and protection against rust. In addition, Mobilgrease CM-P and Mobilgrease CM-L contain 3% molybdenum sulphide for additional wear protection. Other formulation features provide low-temperature dispensing, very good resistance to water wash, and long service in bearings operating at high temperatures. These heavy-duty, severe-service greases have outstanding structural and chemical stability. Mobilgrease CM Series products won't corrode steel or copper-bearing alloys and are compatible with conventional seal materials.

Mobilgrease CM greases are recommended for construction and mining sector applications, as well as heavily loaded industrial bearings. Mobilgrease CM-P is recommended for highly loaded plain and antifriction bearings and other applications where the three percent molybdenum disulphide and high-temperature thickener system will provide extraordinary performance. Mobilgrease CM-S is recommended for the lubrication of plain and antifriction bearings in contractor and mining vehicles working under severe operating and weather conditions. The recommended application temperature range for Mobilgrease CM-P and CM-S is -20° C to +175° C. Mobilgrease CM-L and CM-W are winter-grade products and are recommended for cold-temperature service. The recommended application temperature range for Mobilgrease CM-L and CM-W is -30° C to +175° C.

Features and Benefits

Mobilgrease CM Series greases are leading members of the Mobilgrease brand of products, which has gained a world-wide reputation for innovation and performance excellence. Mobilgrease CM Series grease products are designed by our formulation technologists and backed by our world-wide technical support staff.

Mobilgrease CM Series greases are designed specifically to meet the needs of customers with heavily loaded equipment that require high EP/antiwear performance which remain in place even in tough conditions of water wash, high sliding and high temperature. These greases are targeted especially for the severe construction and mining sector and offer the following features and potential benefits:

Features	Advantages and Potential Benefits
Excellent resistance to water, including spray	Maintains excellent lubrication properties and protects equipment in conditions of water contamination
Very good EP and anti-wear protection	Lower maintenance costs and less unanticipated downtime
Better stay-put properties at high temperatures	Excellent performance in high shear, high load applications, especially where grease re-supply is limited
Resists rust and corrosion	Protects equipment in presence of water for reduced maintenance and longer equipment life



Features	Advantages and Potential Benefits
Good pumpability at low temperatures	Excellent low temperature properties including start-up in remote locations

Applications

The Mobilgrease CM family of products are highly recommended for heavily loaded applications or environments highly contaminated with water, especially in the contractor / mining sector. Specific examples of such applications include:

- Heavy-duty trucks especially, hinge and bucket pins
- Mining and construction equipment
- Highly loaded plain and antifriction industrial bearings

Specifications and Approvals

Mobilgrease CM Series meets the following industry specification:	CM-L	CM-P	CM-W	CM-S
DIN 51825: (2004-06)		KPF2N-20		

Typical Properties

Mobilgrease CM	CM-L	CM-P	CM-W	CM-S
NLGI Grade	1	2	1	2
Thickener Type	Li-Complex	Li-Complex	Li-Complex	Li-Complex
Color, Visual	Grey	Grey	Orange	Orange
Penetration, Worked, 25° C, ASTM D 217, mm/10	325	280	325	280
Dropping Point, °C, ASTM D 2265	260	260	260	260
Viscosity of Oil, ASTM D 445				
KV @ 40° C	150	320	150	320
Penetration Consistency Change, ASTM D 1831, mm/10	-15	-3	-15	-4
Timken OK Load, ASTM D 2509, lb	45 (min)	45 (min)	40 (min)	40 (min)
4-Ball Wear Test, ASTM D 2266, Scar, mm	0.5	0.5	0.5	0.5
Corrosion Prevention, ASTM D 1743, Rating	Pass	Pass	Pass	Pass
Copper Strip Corrosion, ASTM D 4048	1A	1A	1A	1A
Water Washout, ASTM D 1264 1 hr. @ 79° C, %	12	6	12	6

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product



should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus design are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.